

The PB Series features modern, rugged enclosures made of glass fiber reinforced Polycarbonate, designed to protect and insulate 22.5 mm push buttons in dusty, corrosive and wet environments. Five different standard enclosures have predrilled mounting holes for up to five switches. Custom enclosures are available in different sizes and hole patterns to suit your specific application. Call Altech for further information.

- Universal fit for nearly all 22.5mm dia. push buttons
- Compatible with the EK and TK Enclosure Series
- Customization services available design and quantity considerations may apply
- Proven technology with modern design
- Black cover screws are standard with all models
- IP66 / Nema 4X
- UV, weather and impact resistant

## **PB** – Polycarbonate - Push Button Enclosures

## Altech

## **Standard Features**

• Protection Level: IP66\*

• **Technical:** M16/20 Knockout Sidewalls<sup>1</sup>

22.5 mm Diameter Push Button Holes

UL Recognized

Enclosure Material: Polycarbonate

Material

Temperature Range: -40°C to 120°C (-40°F to 248°F)


Gasket Material: Polyurethane
Color: Light Gray
Accessories: See section below


\* IP66 when suitable installation devices are used.





## PB


Ordering	Dimensions mm (in)					Std.
Information	Cat. No.	Type	Length	Width	Height	Pk.
One Button Enclosure	153-901	PB1-L	94 mm (3.70 in)	94 mm (3.70 in)	81 mm (3.19 in)	1
Two Button Enclosure	153-902	PB2-L	130 mm (5.12 in)	94 mm (3.70 in)	81 mm (3.19 in)	1
Three Button Enclosure	153-903	PB3-L	180 mm (7.09 in)	94 mm (3.70 in)	81 mm (3.19 in)	1
Four Button Enclosure	153-904	PB4-L	180 mm (7.09 in)	94 mm (3.70 in)	81 mm (3.19 in)	1
Five Button Enclosure	153-905	PB5-L	180 mm (7.09 in)	94 mm (3.70 in)	81 mm (3.19 in)	1











<sup>1</sup> Consult Altech for knockout location and quantity.